

FIELD SEASON 1980-81 TO 83-84

GEOTECHNICAL REPORT ON THE JAMUNI DAM PROJECT,
GOLA RIVER, NAINITAL DISTRICT, UTTAR PRADESH

(WITH EIGHT PLATES)

BY

R.V. IYER

R. ANBALAGAN

L.K. SANWAL

GEOLOGICAL SURVEY OF INDIA

FIELD SEASON 1980-81 TO 83-84

GEOTECHNICAL REPORT ON THE JAMUNI DAM PROJECT,
GOLA RIVER, NAINITAL DISTRICT, UTTAR PRADESH

(WITH EIGHT PLATES)

BY

NOT TO BE PUBLISHED WITHOUT THE PRIOR PERMISSION OF THE
DIRECTOR GENERAL, GEOLOGICAL SURVEY OF INDIA.

R.V. IYER

R. ANBALAGAN

L.K. SANWAL

GEOLOGICAL SURVEY OF INDIA

GEOTECHNICAL REPORT ON THE JAMRANI DAM PROJECT GOLA RIVER,
NAINITAL DISTRICT, UTTAR PRADESH.

By

R.V. Iyer, R. Anbalagan & R.K. Sarwal

c o n t e n t s
C O N T E N T S

<u>CHAPTER</u>	<u>TITLE</u>	<u>PARAS</u>
I	ABSTRACT	
I	INTRODUCTION	1
II	REGIONAL GEOLOGY AND SEISMICITY	2-4
III	GEOLOGY OF THE DAM SITE	5-17
IV	GEOTECHNICAL PROPERTIES OF ROCKS	18
V	AVAILABILITY OF CONSTRUCTION MATERIAL	19-32
VI	CONCLUSIONS AND RECOMMENDATIONS	33-43

APPENDICES

- | | |
|-----|--|
| I | Results of In-situ cyclic plate load test. |
| II | Results of flat jack test. |
| III | Results of in-situ shear tests. |
| IV. | References. |

List of Plates :

- | | |
|-------|--|
| I. | Regional Geological map of the area around Jamrani Dam site, Nainital District, U.P. |
| II. | Photogeological and geomorphological map of the area around Jamrani dam site. |
| III. | Geological map of Dam site. |
| IV. | Geological section along the proposed Dam axis. |
| V. | Stereoplots of bedding and Joint planes at Dam site. |
| VI. | Geological log of Drill hole No-21. |
| VII. | Geological log of Drill hole No-25. |
| VIII. | Map showing tentative depths of clay in 'K', L-X and 'L' areas. |

X-X-X-X-X-X-X-X

(Field Season 1980-81 to 1983-84)

GEOTECHNICAL REPORT ON THE JAMRANI DAM PROJECT,
GOLA RIVER, NAINITAL DISTRICT, UTTAR PRADESH.

(With Eight Plates)

By

R.V. Iyer, R. Anbalagan & R.K. Samal

Geological Survey of India

A B S T R A C T

- i) Geotechnical investigation for a dam across Gola river near Jamrani village, Nainital district, U.P. for irrigation and drinking purposes were continued in the period under reference.
- ii) The proposed dam site is located on sandstone alternating with minor siltstone/claystone bands brought in contact with a thrust (Krol thrust) a little north of the dam site. In view of the project area lying in the seismic zone IV of the Indian sub-continent and also because of the nearness of the Krol thrust to the proposed dam site, it is warranted to duly provide for necessary seismic factor in the design for the safety of the structure.
- iii) The proposed site is prima facie suitable for a concrete as well as a rock fill dam. Sufficient quantities of construction material for both the types of dam are also likely to be available in the project area. However, for a rockfill dam with clay core, the major geotechnical problem would be the location of spillway. In case of a concrete dam, the foundation grade rocks of varying physical properties will have to be adequately treated to render them monolithic to ensure against differential settlement. Type of the dam has to be decided.
- ii) The proposed dam site is located on sandstone alternating with minor siltstone/claystone bands brought in contact with a thrust (Krol thrust) a little north of the dam

INTRODUCTION :

1. The feasibility stage geological investigations of the proposed Jamrani Dam Project were commenced in 1973. A number of progress reports and study notes covering various geotechnical investigations on the project have been issued since then. The present report incorporates the geotechnical data collected by the authors during the field seasons 1980-81 to 1983-84, against item No. EG/53 O/NR/UP/73/73 of approved field programme of Geological Survey of India for these field seasons. The investigations during field season 1980-81 were attended to by the first author (136 days), during 1981-82 by the second and third authors (76 days and 110 days respectively) and during 1982-83 and 1983-84 by the second author (296 days and 237 days respectively). The work done comprised :

Field season	Detailed mapping (1:1000 scale)	Traverse mapping 1:63,360/50,000 scale.	Prep. of geol. section 1:1000	Pit logg-ing.	Drift logg-ing 1:100	Drill hole core logg. exam.
--------------	---------------------------------	---	-------------------------------	---------------	----------------------	-----------------------------

INTRODUCTION :

1980-81 0.06 sq.km. 26 L.km. 810 L.m. 53.4m 16m 53.5m
 1981-82 0.35 sq.km. 7.5 L.km. - - - - -
 1982-83 & 1983-84 0.241 sq.km. 78 L.km. - - - - -
 Mapping on :
 (i) 1:8000 scale = 0.652 sq.km.
 (ii) 1:7500 scale = 0.7 sq.km.
 No. of field tests attended = 49 during 1980-81
 In-situ test-site mapping = 10 sq.m., during 1981-82
 In 1980-81 Field season, reconnaissance traverses were also taken in the new Janibagh Dam site area of Jamrani dam project when cores of drill holes I and II driven to 22.5m and 35m respectively on right bank were examined. The hole II encountered bed rock at 30.5m depth.

2. The project envisages construction of a dam across Gola river near Jamrani village (29°16' : 79°36' 36" ; 530/11) Mainital district, U.P. The height of the dam was originally proposed to be 145m. The same has subsequently been reduced to 130m (in 1982-83). Also, the initially proposal to have a rock fill dam with a central clay core, a chute spillway on the right bank and a diversion tunnel on the left bank, received a set back when doubts were raised about the availability of clay core material in the dam site area. However, presently two alternatives, viz a rock fill dam with clay core and concrete dam, are under consideration.

The proposed dam is to be located on the Lower Siwalik rocks (comprising mainly sandstone alternating with siltstone & claystone) which are juxtaposed along the Krol thrust, with granite gneiss towards north in the project area. The presence of the thrust in the vicinity of the dam, the location of the project area within seismic zone-IV of the tethian sub-continent warrant the provisions of seismic fact in the design for safety of the structure.

4. The geological investigations done so far indicate that the proposed dam site is prima facie suitable for a rock fill as well as a concrete dam. Construction material for both of the structure is also likely to be available in sufficient quantities within reasonably short distance from the dam site. Type of the dam is yet to be decided.

5. The investigations were carried out under the overall guidance and supervision of Sri K.N. Srivastava, Director, Engineering Geology division (East) Geological Survey of India and Sri B.K. Aalok, Geologist (Sr.) and Party Chief on Projects, Dehradun, who visited the project in March, 1984 and June 1984 and extended suggestions in preparation of the report. The author thankfully acknowledge the facilities and co-operation extended by the project authorities.

II- REGIONAL GEOLOGY AND SEISMICITY :

6. Regional geological mapping of the area around the project was done by S.P. Nautiyal (1943-44). The tectonic sequence of the rocks encountered in the area from north to south (Jangpangi, et.al. 1969-70) is as given below :-

	Ramgarh Thrust	
		Gritty quartzite, pink quartzite pabbly at base, purple and green slates, phyllonites and pink-siliceous limestones with basic acidic intrusives and extrusives.
Bhimtal Formation		
	Krol Thrust (Main Boundary Fault)	
Lower Siwalik Formation		Sandstone, siltstone, claystones and pseudoconglomerates.

3. The prominent structural features of the project area are Krol thrust (Main Boundary Fault), and faults trending NW-SE, N to NNW-S to SSE and NNE-SSW. The Krol thrust, a major tectonic feature of Himalaya, is well defined in the area, where rocks of the Shivalik Formation are thrust over the Yammur Lower Siwalik along it. (Plate-I). The thrust generally dips at an angle of 40° to 50° towards north. Its nearest trace is about 500m from the Jammur dam site on the right abutment. It is also exposed in the reservoir area about 3.5km away from the dam site. The thrust zone is mostly covered with debris. Aerial photo studies conducted by Chhibber (1977) indicate definite evidence of tectonic activity along the thrust plane on the right bank of Luger gad close to its confluence with Gola river, where it has caused several vertical displacements (Plate-II).

8. For monitoring movements, if any, along the thrust plane a number of survey pillars have been established on both of its sites, and precision levelling observation taken in 1982 by Survey of India. It is felt that for meaningful results, these observations should be taken periodically, at least once in a year. It is apprehended that some of the precision levelling pillars may not give correct picture because of their installation at rather unfavourable locations. One such pillar is located just near the edge of the steep rock slope about 30m downstream of the dam axis on the right bank, where presence of open joints can cause its settlement. It is always preferable to secure the pillar with the in situ rock to ensure that the movements recorded are those of bed rock. Incidentally, the dam site is located in seismic zone IV and as such suitable seismic factors should be incorporated in the design of the dam.

III. GEOLOGY OF THE DAM SITE :

9. The geological mapping of the dam site on 1:10,000 scale carried out earlier was not duly controlled due to non-availability of a detailed contour map. This necessitated further work and accordingly revised detailed mapping of the site on the Survey of India topographic sheets has been in progress taken up since 1981. A total of about 0.84 sq.km area had been geologically mapped since 1973. This includes 0.17 sq.km covered during 1983-84.

The proposed Jaurani site is located on the lower Sivaliks which consist of sandstone with alternate bands of siltstone and claystone. These generally trend in NW-SE direction with dip of 30° to 50° towards NW (i.e. upstream) direction. They are traversed by a number of joints which when plotted on a stereonet give the following centres of concentrations (Plate-V).

STRIKE

DIP

REMARKS:

- | | | |
|--------------------------------|---------------------------|-------------------------|
| 1. $N39^{\circ}W-S39^{\circ}E$ | $40^{\circ}/N51^{\circ}E$ | Bedding joint |
| 2. $N20^{\circ}E-S20^{\circ}W$ | $60^{\circ}/N62^{\circ}W$ | Joint (J ₁) |
| 3. $N65^{\circ}E-S65^{\circ}W$ | $59^{\circ}/S25^{\circ}E$ | Joint (J ₂) |
| 4. $N50^{\circ}E-S50^{\circ}W$ | $60^{\circ}/N40^{\circ}W$ | Joint (J ₃) |
| 5. $N50^{\circ}W-S50^{\circ}E$ | $51^{\circ}/S40^{\circ}W$ | Joint (J ₄) |

The bedding and joints control the drainage and topography on either bank and are also responsible for major landslides in the area.

11. Joints are well developed in the sandstone which is grey or brown coloured and fine to coarse grained. Concentration of biotite along the bedding planes of the sandstone renders it flaky. At places, it is friable due to poor cementation. The claystone is grey, brown or purple colour. At its contacts with sandstone it shows effects of shering 10 to 15 cm. It is highly weathered near the surface. The siltstone is dark grey coloured and usually well cemented and hard. It is micaceous at places.

12. The topography on the left bank is guided by the dip slope of the beds and the alternate arrangement of the different bands is not very conspicuous, except where these have been differentially eroded. It is characterised by ridges and depressions marked by wide galas (Plate-III). The erosion by the stream has caused several slips, both in the upstream and downstream of the dam axis.

13. The slope on the right bank of the river is controlled by a joint set dipping at 50° to 70° towards west (i.e. valley side). The ridges and depressions, formed due to differential weathering and erosion of alternating sandstone and claystone bands, extend across the dam axis. Slope failures have taken place where the toe of rock mass controlled by the south-westerly dipping joints is eroded and overhangs created.

14. The dam axis on the left bank is located on a 40m to 50m wide ridge of sand stone above El_z 65m which extends upto the top of the dam. The dam at its top will have a length of 427m of which 69m lies in the river bed, 217m on the left banks and 141m on the right bank. The entire river bed is covered by river borne boulders and sand. The rock outcrops are seen on the abutments only.

IV. GEOTECHNICAL PROPERTIES OF ROCKS :

15. To determine the geotechnical properties of rocks. The following in-situ tests were got done by Central Soil Material Research Station (CSIRS), New Delhi.

i) Cyclic Plate Load Tests :

To study the deformation characteristics of rocks 'cyclic plate load tests' were carried out at fifteen locations on the right bank. The results as given in Memorandum No 2-3 (February 1981) are tabulated in Appendix-I. The analysis of the results reveals that the modulus of deformation for sandstone near the river bed varies from $0.008 \times 10^5 \text{ kg/cm}^2$ to $0.072 \times 10^5 \text{ kg/cm}^2$ and in the drift No R-I, from $0.021 \times 10^5 \text{ kg/cm}^2$ to $0.174 \times 10^5 \text{ kg/cm}^2$. For claystone, near the river bed, it varies from $0.008 \times 10^5 \text{ kg/cm}^2$ to $0.11 \times 10^5 \text{ kg/cm}^2$ and the drift from $0.033 \times 10^5 \text{ kg/cm}^2$ to $0.251 \times 10^5 \text{ kg/cm}^2$. For siltstone, near the river bed, it is $0.024 \times 10^5 \text{ kg/cm}^2$.

ii) Flat Jack Tests :

17. Six numbers of 'flat jack tests', three each on sandstone and claystone, have been carried out. The results are tabulated in Appendix-II. The values of modulus of deformation obtained from horizontal slots and vertical slots does not show appreciable difference in sandstones. Most of the values vary from $0.05 \times 10^5 \text{ kg/cm}^2$ to $0.081 \times 10^5 \text{ kg/cm}^2$. For claystone, the modulus of deformation obtained from vertical slots ranges from $0.0227 \times 10^5 \text{ kg/cm}^2$ to $0.0256 \times 10^5 \text{ kg/cm}^2$, and is $0.0113 \times 10^5 \text{ kg/cm}^2$ for the test conducted in Horizontal slots.

18. From the above it is evident that the values of modulus of deformation for sandstone, siltstone and claystone do not show appreciable difference. The poor value may be due to the selection of unfavourable test sites. Further since most of the tests were carried out under dry conditions, there may be significant reduction in the respective values under saturated condition (when the reservoir is full).

It is understood that the above two tests carried out subsequently have indicated good values of bearing capacity. The same may be made available for analysis.

iii) In-situ shear Test:

19. Two number of tests were carried out for rock over rock, one each for claystone and sand stone. Three number of tests were carried out for concrete over rock, one each for sandstone, siltstone and claystone, using 70cmx70cmx35cm size block of concrete. The results are tabulated in Appendix -III.

20. The compressive strength of sandstone varies from 214 kg/cm² to 432 kg/cm² under dry conditions and from 204 kg/cm² to 218 kg/cm² under wet conditions. For siltstone, it is 513 kg/cm² under dry conditions. The compressive strength of claystone has not been determined. Tests for the same, under dry and saturated conditions, may be conducted for better appraisal.

V. SUB-SURFACE EXPLORATION :

i) Drifting :

21. To explore the abutment conditions, two drifts DR-1 (El 692m) and DR-2 (761m) have been excavated on the right abutment for 37.5m and 33m respectively. In general, they have encountered good rock and have been self supporting even after the collapse of timber supports. The lateral depth to sound and fresh rock in them is 24m and 18m respectively. The approximate depth of weathering may be of the order of 10 to 15m.

22. On the left abutment also two exploratory drifts i.e. DL-1 (El 639.6m) and DL-2 (El 771.0m), have been put in sandstone. Their respective lengths are 35.5m and 34m. The drift DL-1, has been unfavourable aligned very close to a nala and as such it has not established the lateral depth of sound rock. In the drift DL-2, sound rock is available after 15m. The expected depth of stripping of abutment may be 13 to 15m.

11) Drilling :

23. In all 22 drill holes have been put in the dam site area. Logging of the first 20 holes drilled before 1981 could not be carried out as the cores have not been found in order. Two drill holes, DH No-21 on left abutment and DH No-25 on right abutment have been drilled from El 645.3m, and El 644.85m respectively after December 1982 to probe the foundation rock. Both these holes are located close to the river bed and have been drilled to depths of 70m and 69.5m respectively (Plate VI & VIII). Before 1981 five drill holes have been put in each on either abutments and three in the river bed section. From the available data only the depths of overburden encountered by these drill holes, may be determined.

24. Thick bands of sandstone, with alternate siltstone and claystone bands have been encountered in the holes drilled recently. Siltstone is hard and compact and individual bands ranges in thickness from 1 to 8m, claystone bands are less than 2.5m in thickness. Weathering effects have been seen upto a maximum depth of 9.5m.

25. In DH-21, the percent core recovery is generally good. It ranges from 40% to 60% upto 18m and more than 70% further down. The Rock Quality Designation (RQD) is poor upto the depth of 18m, but further down, it is good (75% to 90%) to excellent 90% to 100%.

26. In DH-25, the percent core recovery is generally more than 50% down to the depth of 39.5m and further down more than 70%. The RQD is generally poor (25% to 50%) upto the depth of 54.5m, except for short reaches, where it is fair (50% to 75%). Further down it is good to excellent.

27. The water percolation tests carried out in the holes indicate that permeability in general decreases with depth. It ranges from 10 to 30 lugeons down to 35m depth and comes down to less than 10 lugeons further beyond. It is felt that a few more drill holes along the dam axis may have to be done for better assessment of foundation conditions.

VI. AVAILABILITY OF CONSTRUCTION MATERIAL :

1. Concrete Gravity alternative :

23. It has been estimated that the total required quantity of 20 Lac m³ of coarse and fine aggregates would be available in the river bed within 3km downstream of the dam site.

2. Rock fill alternative :

29. The estimated required quantities of construction materials are as follows :

i) River borne material	= 22.70 lac m ³
ii) Crushed rock	= 28.94 lac m ³
iii) Clay core	= 9.90 lac m ³
iv) Graded filter	= 10.70 lac m ³

It is understood that the total requirement of river borne material is available within 5kms of the dam site. The filter material is also proposed to be obtained by screening the river borne material. The crushed rock is proposed to be quarried from Barajala about 2.5kms downstream of the dam site.

30. Position regarding availability or otherwise of clay core material in sufficient quantity has been doubtful till recently. A preliminary survey of a number of prospective areas has lately been undertaken, which has shown encouraging results. It has been decided to establish 20 lakh m³ of clay core material so that the required quantity of about 10 lac m³ of clay may be recovered from them after accounting for the losses due to stripping, borrows and transit and quality control rejects. In this connection five borrow areas, namely 'K' 'L' 'L-X' 'A' and 'G' are presently under consideration of the project authorities. Preliminary geological investigations of all these areas, except 'A' area, for estimation of clay reserves have also been carried out. Preliminary geological mapping of 'K' 'L' & 'L-X' areas has been carried out covering a total area of about 0.65 sqkm on 1:50,000 scale (Plate-VIII).

31. The clay available in these areas is of heterogeneous variety. In fact, the clay to silt size fractions, which form about 40% to 60% of the bulk of the amount are found mixed with rock pieces, ranging in size from few cms to about 1.0m. These rock pieces/blocks are generally of sandstone.

32. It has not been possible to establish the depth of clay reserves in these areas so far, because systematic explorations by means of pits, could not be implemented due to non availability of land, mostly under terraced cultivation. Other sub surface data available is also inadequate. Therefore the depth of clay taken for the purpose of calculation of reserves is mainly based on geological mapping and geomorphological setting of the areas. The probable average depths

for individual blocks are indicated in the map and the same will have to be ascertained by systematic explorations. The prospective areas are individually discussed in the following lines :

1) 'K' area : -

33. It is located about 50m downstream of the dam axis to the left of the Gola river, between El $\pm$ 640m and El $\pm$ 640m. A northeasterly flowing nala marks the boundary towards north. Further, the area is dissected by two ephemeral nalas roughly flowing towards North. Terraced cultivation is being carried out partly in the prospective area.

34. It is understood that a total of 11 pits have been excavated in this area, upto El $\pm$ 710m, to depths ranging from 1.5m to 5.05m before 1932. But they are of little help in reserve calculations since they have not been deepened down to bed rock level. Also the records regarding their location, the type of material encountered in them etc. have not been properly maintained.

35. The depth of clay, indicated in the map (Plate-VIII) tentative and will have to be substantiated by systematic subsurface explorations. However, the preliminary investigations indicate a total reserve of about 12,20,000 m³. Based on the visual estimation, 40% of the total reserve has to be deducted to account for the excessive oversized rock blocks/boulders. This leaves the clay core grade reserve of the order of 7,32,000 m³. The estimate, it is felt, is modest, and the detailed explorations are expected to prove more than the above inferred reserves.

'L-X' area :

36. This area is located in the northern vicinity of 'K' area, beyond the northeasterly flowing nala. Separating these two areas from one another. It is bounded by another Easterly flowing nala towards north. The area lies between El $\pm$ 640m and El $\pm$ 850m. The slope generally has a thin cover of overburden comprising clay and abundant rock blocks/boulders. In-situ rock exposures are also observed at places in the nala cuts.

37. Based on the geomorphology of the area, two prospective locations have been demarcated for further explorations. Though no subsurface explorations have been carried

out in that area so far, it is felt that the thickness of clay in these locations may be more than 6m. (140% for the oversized fractions from the estimation of clay reserves, the core grade clay available in the two locations may be 2,77,000 m³.
'L' area :

39. It is located to the North of 'L-X' area and is an easterly flowing nala and lies between El+635m and El+755m (Plate-VIII). Part of the area is supporting terrace cultivation. It is understood that a total of 18 pits have been excavated here so far. However the required details of as many as 17 pits excavated before 1982 are not available. A solitary pit located at El+635m to a depth of 7.5m during 1983 was located close to easterly flowing nala. Clay with good plasticity is encountered in the entire depth of the pit which has not yet reached the bed rock level. Boulder size fraction (as 6mm) is more (about 40%) near the surface, while below 6.5m dark grey coloured clay with less than 10% of coarser size fraction, is exposed till the bottom. The estimated core grade clay reserves, after deducting 40% for oversized material, are about 3,08,000 m³ in this area.

'G' area :
40. This area is located about 6km downstream of the dam axis to the left of Gala river between El+604m and El+920m. The area towards East and West is bounded by N-S trending ridges and towards South by E-W trending ridge. These ridges have in-situ rock exposures. Two major nalas and a number of minor ones are draining the area. The prospective area has a slope of the order of 20° to 30° towards north with the vegetation.

41. It is understood that a number of pits were excavated in the area before 1981, the records of which are not available. However, 12 pits have been excavated during 1983-84 most of them to depths ranging from 6.0 to 9.0m. None of them has touched the bed rock. Though the detailed geological mapping of the area is yet to be taken up, a preliminary assessment of clay reserves has been attempted on the basis of traverses. The total prospective area, calculated from the topographical map is about 7 lacn². Assuming an average thickness of clay to be 6m and deducting 50% for the oversized

fractions, the core grade clay reserves may be about 21 lakh m²

'A' area :

42. This area is located about 6km downstream of the dam axis to the right of the Gola river, above the Kathgodam-Jaurani road. A number of pits have been excavated in this area before 1982. One of the pits located close to the road, has, on examination, indicated clay of good P.I. value (3) with less than 20% of oversized boulders. Further systematic explorations may prove the potentiality of the area.

VII CONCLUSIONS AND RECOMMENDATIONS :

43. Geotechnical investigations of Jaurani dam project, which envisages construction of a 130m high storage dam for irrigation purpose, have been in progress since 1973.

44. The Lower Siwalik rocks towards north are in contact with granite/basic rocks along the Krol thrust. The thrust is exposed about 0.5km towards north of the dam site. It also passes through the reservoir area about 3.5km from the dam site. It is believed to have been activated in the recent times. It is suggested to monitor the movements, if any, along this plane, periodically by precision levelling. For quantitative estimation of water loss along this plane under impoundment conditions, the earlier suggested inclined drill hole across the thrust plane and water pressure tests in the thrust zone, may be taken up.

45. The rocks exposed at the dam site comprise sandstone with alternate bands of siltstone and claystone, belonging to Lower Siwalik Formation. These generally trend in NW-SE direction with dips of 30° to 55° towards NE direction and are traversed by a number of joints.

46. The subsurface exploration at the dam site includes 4 drifts and 22 drill holes. However only two drill holes could be logged thoroughly. Scanty data that could be gathered from other drill holes could only be used to mark the overburden/rock contact. At least four more drill holes each about 50m deep, need be drilled along the dam axis two in the river bed and one each on either abutment for probing the foundation grade rock conditions.

47. The water percolation test results indicate the need for curtain grouting at the foundation grade. It is suggested to carry out grouting tests at that level, for evaluating groutability of rocks there.

48. The values of modulus of deformation obtained from in-situ cyclic plate load tests for rocks near the river bed are lower as compared to those inside the drift No DR-1 indicating physically better rock in the drift. However, the modulus of deformation values obtained from plate load tests do not show appreciable difference for sandstone, siltstone and claystones though those obtained from flat jack tests are better for sandstone than for claystone.

49. An analysis of compressive strength of sandstone and siltstone core samples, as determined in laboratory, shows reduction in values by about 30% to 50% under wet conditions. Since all the insitu tests were carried out under dry conditions, there may be significant reduction in the values under saturated conditions, when the reservoir is full. It is suggested that in situ and laboratory tests under dry and saturated conditions may be carried extensively at the sites of various components of the dam. Claystone too may be subjected to the tests.

50. The engineers and geologists have been working on the suitability of the type of dam and a number of proposals have been considered from time to time. However, presently only two alternatives namely rock-fill dam with clay core and concrete dam are being actively considered. The proposed site is prima facie suitable for both a concrete as well as a rock fill dam. Type of the dam may be decided so that further geological investigations are planned accordingly.

51. For rock-fill dam, the major geotechnical problem is the spillway which is imposing serious design and execution problems due to unfavourable geological and topographical conditions. The excavations on the left abutment are likely to cause dip slope failures and will require extensive protective treatments. While on the right abutment having steep valley slopes above the top of the dam, construction of spillway may involve huge excavations with connected slope stability problems.

52. Though this problem can be solved by having a concrete dam with overflowing spillway, the main problem lies in the foundation treatments, since the foundation grade rocks have varying physical properties. The claystone bands, which become more plastic under saturated conditions, may form about 20 to 25% of the bulk rock mass at foundation grade. The width of claystone bands varies from 1 to 3m. They will require adequate treatments in case of concrete dam. Further grouting tests, to be carried out, may bring out groutability characteristics of the rocks as well as the improvements, if any, in the bearing capacity of the foundation rocks. It is understood that the plate bearing tests carried out recently have indicated good values of bearing capacity.

53. Sufficient quantities of the construction materials for the concrete gravity dam alternative are available within 3 km downstream of the dam site. For rock-fill dam alternative also, all construction materials, except clay, are available in sufficient quantities within 5 kms from the dam site, to be obtained from the river bed and a quarry. The preliminary geological investigations indicate that the required quantity of clay for clay core may be available from 'K' 'L-X' and 'L' areas located in the downstream vicinity of dam site. The shortages, if any can be, met with from 'A' and 'G' areas, about 6 kms away from the dam site.

54. The clay deposits under investigation occur along the hill slopes which are generally thickly vegetated. Excavation for clay may trigger landslides due to removal of the material. As such, the excavation has to be carefully planned and executed to avoid/minimise environmental hazards in the area.

Sd/-

Sd/-

Sd/-

(R.V. IYER)

(R. ANBALAGAN)

(R.X. SANWAL)

-X-X-X-X-X-X-X-X-

APPENDIX-I

RESULTS OF IN-SITU CYCLIC PLATE LOAD TEST

Sl. No.	Location/Type of Test	Cycle No.	Load in Tonnes	Stream in 2 kg/cn	Gross deflection in cm	Permanent settlement in cm	Plastic Deflection in cm	$\frac{P}{A}$ kg/cn ² x 10	$\frac{P}{A}$ kg/cn ² x 10	$\frac{P}{A}$ kg/cn ² x 10	$\frac{P}{A}$ kg/cn ² x 10
1.	River side RT BANK VERTICAL SANDSTONE 'B'	I II III	16 32 50	12.37 25.47 39.79	0.598 0.999 1.483	0.556 0.895 1.277	0.042 0.104 0.266	0.007 0.008 0.008	0.095 0.077 0.061	13.57 9.63 7.63	
2.	River Side RT BANK VERTICAL CLAYSTONE 'A'	I II III IV	10 20 40 50	7.95 15.92 31.83 39.79	0.307 0.615 1.103 1.415	0.282 0.511 0.851 1.106	0.025 0.204 0.252 0.309	0.008 0.008 0.009 0.009	0.098 0.048 0.044 0.040	12.40 6.0 4.44 4.44	
3.	River Side RT BANK VERTICAL SANDSTONE 'C'	I II III	12 20 45	9.55 15.92 35.81	0.080 0.149 0.323	0.074 0.117 0.233	0.009 0.032 0.09	0.036 0.033 0.035	0.33 0.156 0.125	5.24 4.66 3.56	
4.	River Side RT BANK VERTICAL SANDSTONE 'D'	I II III	12 32 47	9.55 25.46 37.40	0.189 0.374 0.486	0.173 0.325 0.383	0.016 0.049 0.191	0.0158 0.021 0.024	0.187 0.163 0.114	11.85 7.76 4.74	

[illegible]

Тенаркэ І

T = Max. load in kg.; W_0 = Deformation in cm. corresponding to load.

$$\text{Pa} (1-u^2)$$

$n = \text{a constant} = 0.96$ for circular plates, $\eta = \text{poisson's ratio} = 0.28$

 $\frac{M}{CM} = F$

A = Area of plate in cm^2 , E_d = Information modulus corresponding to

7 / CM

$A =$ Area of plate in cm², $E_d =$ Indentation modulus corresponding to cross deformation

xxxxxx Modulus of elasticity corresponding to elastic deformation.

RESULTS OF FLAT JACK TEST

APPENDIX-II

Sl. No.	Location/ Type of test	Cycle No.	Stress in kg/cm ²	Gross deformation mm	Permanent settlement mm	Elastic deformation mm	E _u kg/cm ²	E _s kg/cm ²	E _t kg/cm ²	E _u /E _s	E _t /E _s
1.	FJT-1 HORTZ SLOT (Claystone)	1	1.5x10.52	0.4618	0.1891	0.2726	0.0113	1.5x10.52	0.0194	1.69	0.2726
2.	FJT-2 VERT. SLOT (Claystone)	1	4 x 10.52	0.3304	0.1936	0.1368	0.025	4 x 10.52	0.061	2.44	0.1368
3.	FJT-3 VERT. SLOT (Claystone)	1	3 x 10.52	0.2438	0.0828	0.161	0.0256	3 x 10.52	0.039	1.52	0.161
		2	4 x 10.52	0.3668	0.1513	0.215	0.0227	4 x 10.52	0.0588	1.71	0.215
4.	FJT-4 VERT. SLOT (SANDSTONE)	1	3 x 10.52	0.0066	0.021	0.0556	0.081	3 x 10.52	0.112	1.37	0.0556
		2	6 x 10.52	0.1581	0.0474	0.1086	0.08	6 x 10.52	0.115	1.43	0.1086
		3	9 x 10.52	0.236	0.058	0.178	0.03	9 x 10.52	0.105	1.32	0.178
5.	FJT-5 V. H.T. SLOT (SANDSTONE)	1	3.5x 10.52	0.145	0.0535	0.092	0.05	3.5x 10.52	0.079	1.58	0.092
		2	5 x 10.52	0.203	0.078	0.125	0.051	5 x 10.52	0.083	1.62	0.125
6.	FJT-6 HORT. SLOT (SANDSTONE)	1	3.5 x 10.52	0.13	0.023	0.107	0.056	3.5 x 10.52	0.068	1.21	0.107
		2	6 x 10.52	0.2308	0.082	0.1688	0.054	6 x 10.52	0.074	1.37	0.1688

APPENDIX-III

TABLE - A

RESULTS OF IN-SITU SHEAR TESTS (ROCK OVER ROCK)

Sl. No.	Type of Test and size	Locat. ion/R.D.	Shear Stress kg/cm ²	Normal stress kg/cm ²	Ratio	Shear Friction parameter
1.	2.	3.	4.	5.	6.	7.
1.	Rock over Rock	21	7.89	3.13	2.52	C=3.14 kg/cm ²
	DR-1 Claystone	22.5	13.8	6.76	2.04	
	70cm x 70cm x 35cm	23.85	12.81	5.47	2.34	$\phi = 58.6^\circ$
		25.3	7.29	2.46	2.96	
2.	Rock over Rock	32.1	11.83	7.25	1.60	
	DR-1 Sandstone	33.55	10.25	3.77	2.72	C=0.3 kg/cm ²
	70cm x 70cm	34.8	14.0	5.79	2.42	$\phi = 69.4^\circ$
	x 35 cm	36.1	17.74	6.28	2.82	

TABLE - B

RESULTS OF IN-SITU SHEAR TESTS CONCRETE TO ROCK

Sl. No.	Type of Test and size	Locat. ion/R.D.	Shear Stress kg/cm ²	Normal stress kg/cm ²	Ratio	Shear Friction parameter
1.	2.	3.	4.	5.	6.	7.
1.	(Siltstone)	21	11.14	11.14	1.0	C = 0.7 kg/cm ²
	DR-4	22.5	4.73	5.35	0.88	
	70cm x 70cm	23.85	2.76	2.78	0.99	$\phi = 39^\circ$
	x 35 cm	25.3	5.42	7.57	0.72	
2.	(Sandstone)	21	5.91	2.1	2.81	C = 79.8 kg/cm ²
	DR-4	22.5	2.96	1.81	1.64	$\phi = 67^\circ$
	70cm x 70cm	25.3	11.83	4.7	2.52	C=2.14 kg/cm ²
	x 35 cm	27.2	11.97	0.53	3.72	
		23.85	12.11	5.47	2.34	$\phi = 50.6^\circ$
3.	(Claystone)	21	8.87	10.54	0.84	C = 2 kg/cm ²
	DR-1	22.5	6.90	5.93	1.16	
	70cm x 70 cm	23.5	4.34	3.25	1.36	$\phi = 40^\circ$
	x 35 cm	23.8	8.87	8.50	1.04	C = 0.3 kg/cm ²
		25.3	17.7	5.72	2.42	$\phi = 69.4^\circ$
		36.1	17.7	6.28	2.82	



APPENDIX-IV

R E F E R E N C E S

1. I & P Circle (March 1974) Jaurani Dam Project
Irrigation Deptt., Volumes 1 to 3.
Bareilly.
2. Dayal, H.M. (April, 1973) A geotechnical note on the
Ranibath and Jaurani dam sites
on Gola river Nainital distt.,
U.P. (with five plates) Unpub-
lished report of GSI for the
field season 1972-73)
3. Dayal, H.M. (Dec. 1973) Second Geotechnical note on the
interpretations of drilling data,
Jaurani dam sites, Gola river,
Nainital distt., U.P. (with three
plates) (Unpublished report of
GSI for the F.S. 1972-73)
4. Dayal, H.M. (Jan. 1974) Third geotechnical note on the
proposed dam and the appurtenant
structure sites and interpreta-
tions of drilling data, Jaurani
dam site, Gola project, Nainital
distt., U.P. (with 3 plates) Unpubli-
shed report of GSI for FS 1973-74)
5. Dayal, H.M. (Mar. 1975) Fourth geotechnical note on the
Jaurani dam project, Gola river,
Nainital district, U.P. (with 7
plates) (unpublished report on
GSI for field season 1973-74)
6. Dayal, H.M. (Feb. 1976) Fifth geotechnical report on the
Jaurani dam project, Gola river
Nainital distt, U.P. (with six pla-
tes) (Unpublished report of GSI
for the field season 1974-75)
7. Jain, M.S. (Mar 1975) A geotechnical review of the
salient features of the Jaurani
dam site, Gola river, Nainital
distt., U.P. (Unpublished report
of GSI)
8. Sharan, R.B. (April 1975) Report on prefield photo-inter-
pretation of Gola catchment area,
Nainital distt., UP for engineering
geological studies (Unpublished
report of photogeology Div, NR, GSI)
9. Dayal, H.M. (March 1976) 6th Geotechnical note on the
Jaurani dam project, Gola river
Nainital distt., UP (with 14th
plates) (unpublished report of
GSI for the F.S. 1976-77)
10. Jaitie, J.M. (April 1979) Geotechnical report on the Jaurani
dam project on river Gola,
distt, Nainital, UP, (Unpublished
report of GSI for the field
season 1979-80)

REGIONAL GEOLOGICAL MAP OF THE AREA AROUND JAMRANI DAM SITE,
NAINITAL DISTRICT, U.P.
(GEOLOGY AFTER S.P. NAUTIYAL, 1943-44)

123



TRACED BY:-
P. Joshi
D/M. J.D.C.D. II


DRG. No. JDP/40 Dt. 18-7-84

(RANBALAGAN)
G.S.I.

PHOTO GEOLOGICAL AND GEOMORPHOLOGICAL MAP OF THE AREA AROUND JAMRANI DAM SITE

(BASED ON UNCONTROLLED MOSASIC & WITHOUT FIELD CHECKS)

SCALE:- 1:70,000 (Approx.)



NOTE:-

Co-ordinates are approximate

INDEX

- T TERRACES.
- PNE TO MEDIUM CLASTICS.
- META SEDIMENTS.
- EXTRUSIVES.

SYMBOL

- PHOTO DIP.
- RIIDGE.
- FAULT.
- SLIDES.

- FAN.
- DAM SITE.
- BREAK IN SLOPE.
- NEOTECTONIC FAULT.

J. S. CHATTERJEE
D.S.A.


DWG. NO. - JAR/39 12-16-78-84

JAMRANI DAM PROJECT
GEOLOGICAL MAP OF DAM SITE





JAMRANI DAM PROJECT GEOLOGICAL SECTION ALONG THE PROPOSED DAM AXIS




- INDEX**
- OVERBURDEN
 - SHALE AND SANDSTONE
 - SANDSTONE
 - CLAYSTONE
 - SILTSTONE
 - LIMIT OF STRIPPING

- NOTES:-**
1. FOR SECTION LINE REFER DRG. NO. JDP/201.12.7.84.
 2. THE SECTION LINE HAS BEEN DEVELOPED FROM SURVEY OF INDIA MAP PROVIDED BY PROJECT AUTHORITIES.
 3. THE AVAILABLE SUBSURFACE DATA HAS BEEN INCLUDED UP TO JULY 1964.
 4. THE LITHO UNITS HAVE GOT PINCHING AND THINNING AS OBSERVED IN THE SURFACE. THEREFORE THE THICKNESS OF VARIOUS BANDS MAY NOT BE UNIFORM.

(211)

JAMRANI DAM PROJECT STEREOPLOTS OF BEDDING AND JOINT PLANES AT DAM SITE



GEOLOGICAL LOG OF DRILL HOLE

PROJECT — Jambani Dam Project

ROLE NO. — 21

STATE — U. P.

BEARING OF HOLE —

FEATURES — Dam Axis Left Abutment, COLLAR EL. 640.30M

HOLE WITH INSTRUMENTATION

STARTED — 14-11-1962

COMPLETED — 2-1-1963

TOTAL DEPTH — 20.0M

TYPE OF BIT USED (With Series)

DEPTH IN METERS	LITHOLOGY		STRUCTURAL SURFACES	DRILL HOLE SIZE	PERCENT CORE RECOVERY	H. & D.	PENETRATION TEST SECTION LOG	SPECIAL OBSERVATIONS AND INTERPRETATIONS
	DESCRIPTION (IN)	LOG						
0	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—
1	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—
2	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—
3	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—
4	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—
5	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—
6	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—
7	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—
8	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—
9	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—
10	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—
11	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—
12	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—
13	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—
14	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—
15	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—
16	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—
17	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—
18	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—
19	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—
20	Medium grained sandstone, yellowish weathered and friable	—	—	—	—	—	—	—

INDEX

- OVERBURDEN
- SAND STONE
- RED STONE
- CLAY STONE
- GRAVEL

- ATTITUDE OF BEDDING
- ATTITUDE OF JOINT
- JOINT PLANE SMOOTH
- JOINT PLANE ROUGH

SCALE — 1 cm = 1 m

BY — H. N. AGARWAL
Geology and Survey of India

GEOLOGICAL LOG OF DRILL HOLE

PROJECT - JERRAH DAM PROJECT

STATE - U. P.

CO-ORDINATES

ELEVATION

FEATURES - DAM AXIS RIGHT ABUTMENT, COLLAR EL. 644.71M

ROAD LEVEL

COMPLETED - 28-1-1984

DATE

TYPE OF BIT USED (with Name)


HOLE NO - 25

BLANKING OF HOLE

ANGLE WITH HORIZONTAL - 90°

TOTAL DEPTH - 48.8 M


DEPTH IN METERS	LITHOLOGY	VEGETATION	DRILL	PERCENT	R. Q. D.	WATER LEVEL	TEST	SPECIAL OBSERVATIONS AND INTERPRETATIONS



JAMRANI DAM PROJECT

MAP SHOWING TENTATIVE DEPTHS OF CLAY IN 'K', 'L-X' AND 'L' AREAS

SCALE-1:8000



INDEX

- DEPTH OF CLAY 8M.
- DEPTH OF CLAY 7M.
- DEPTH OF CLAY 6M.
- DEPTH OF CLAY 5M.

NOTE:-

1. THE TOPOGRAPHICAL MAP HAS BEEN SUPPLIED BY PROJECT AUTHORITIES.
2. THE DEPTH OF CLAY ARE TENTATIVE BASED ON SURFACE GEOLOGICAL AND GEOMORPHOLOGICAL SET UP OF THE AREA AS WELL AS THE EXPLORATION R.P.S.

R. ANBALAGAN
GEOLOGICAL SURVEY OF INDIA